

# Server Configuration

## 4.01 Server Configuration

This section covers all the elements to be configured for running a Liquid UI Server. It consists of following elements:

- [Client PC Configuration](#)  
Configuring SAPGUI on the client PC.
- [Using Liquid UI Server as a SAP Router](#)
- [Configuring Liquid UI Server as a Message Server](#)
- **Server Configuration**

Liquid UI Server is configured by means of the `saproxy.ini` file. The companion SynWatchDog service is configured via the `synwatchdog.ini` file. For Liquid UI configuration, please see the appropriate documentation.

- [saproxy.ini](#)  
Explaining the `saproxy.ini` configuration file.
- [guixt.sjs](#)  
Explaining the `guixt.sjs` configuration file.
- [SynWatchdog](#)  
SynWatchdog is a bundled utility for GuiXT Server.
- [Deactivate GuiXT](#)  
You need to deactivate GuiXT in your SAP GUI as you have configured it in the `saproxy.ini` file.
- [Configure guixt.sjs](#)  
To configure more parameters under `guixt.sjs` file, you need to refer [Configuring guixt.sjs file](#).
- **Restart Liquid UI Server**

Re-start the Synactive R/3 Proxy Service or run the **consolemode.bat** file under Liquid UI Server folder. This file is located in your local drive and path would vary depending upon the Liquid UI Server installed.

For example:

```
For 64 bit OS: C:\Program Files (x86)\Synactive Inc\GuiXTW  
SServer
```

```
For 32 bit OS: C:\Program Files\Synactive Inc\GuiXTServer
```

- You need to check that the Client and the Server are in the **same network** to access the customized screens from the Liquid UI Server.

# Server Configuration

Unique solution ID: #1317

Author: Sarvani Kusuri

Last update: 2019-08-02 09:19